

The Specificities of Foundation Ground Vibrations Induced by Pile Driving Under Conditions of Infill Construction in an Existing City Block

Zaalishvili V.B.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
North Ossetian State University after K.L.Khetagurov
Vladikavkaz, Russia
Complex R&D Institute of RAS
named after Kh.I. Ibragimov
Grozny State Oil Technical University named after
Academician M.D. Millionshtchikov
Grozny, Russia
cgi_ras@mail.ru

Gogmachadze S.A.

Georgian American University
Tbilisi, Georgia

Melkov D.A.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
North Ossetian State University after K.L.Khetagurov
Vladikavkaz, Russia

Chotchaev H.O.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
Vladikavkaz, Russia

Burdzieva O.G.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
Vladikavkaz, Russia

Zaks T.V.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
Vladikavkaz, Russia

Kanukov A.S.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
North Ossetian State University after K.L.Khetagurov
Vladikavkaz, Russia

Gabaraev A.F.

Geophysical Institute - Affiliate of Vladikavkaz Scientific
Centre of Russian Academy of Sciences
Vladikavkaz, Russia

Abstract –Under condition of infill construction pile driving causes an appreciable impact on adjacent buildings, which should be accounted during the works. The work is the first to present the materials obtained in 1990s. The ground was represented by soft and plastic clay with the thickness from 4.5 to 13.0 meters. We considered the specificities of vibrations induced by pile driving into pre-drilled well with smaller diameter, an axially symmetric source. The frequency of vertical vibrations amounted to 18–20 Hz, while horizontal ones amounted to 13–15 Hz. The amplitude of vertical vibrations in the near zone amounted to 0.11–0.413 mm, while in the immediate vicinity, it amounted to 0.0024–0.0061 mm. Besides the solution of the direct problem of effect estimation on existing facilities, the vibration shielding also was considered. The impact with and without the shield was calculated.

Keywords –pile driving; soils; seismic vibrations; spectral content; absorption; site effect.

I. INTRODUCTION

The engineering macroseismic survey of territories in the epicentral area of strong and destructive earthquakes shows that real manifestation of the intensity often differs from forecasted ones. Generally, it is explained by the neglect of a number of effects, including non-linear effects in soils under strong earthquakes, peculiarities of deep structure, relief, type and physical condition of soils, etc. [1–11].

The instrumental measurements are used to estimate the specificities of slight soil movement and forecast the effect of strong ones [12–14]. In this connection, the analysis of soil vibrations induced by pile driving is of great interest [15–18]. Under the conditions of infill construction, the process affects the nearest buildings [19–21].



Fig. 1. Modern residence building built in the experimental spot (image courtesy of S.A. Gogmachadze, 2019).

The Institute of construction mechanics of the Academy of Sciences of Georgia in 1991 has carried out field works on the analysis of vibrations induced by pile driving in the soils of building foundations in Kaloubanskaya and Trialetskaya streets in Tbilisi.

The results are still of relevance. Indeed, the number of accidents and damage events during the construction conditioned by serious miscalculations and errors is of the same amount.

II. IMPACT OF PILE DRIVING ON SOIL

The intensity of vibrations induced by artificial sources, along with other factors, depends on the distance to the impact location. In our case, the smallest distance from piles of constructed building (Fig. 1) altered from 12 to 16 m. The pile driving and soil vibration were measured on the construction site of a high-rise building (Fig. 1).

According to the recommendations [22–23], the impact of soil vibrations on buildings and the value of critical acceleration vary depending on the soil type and their physical condition.

In our case, the soil is presented by soft plastic clay, and its critical acceleration—as per the recommendations—is $a = 150\text{--}220 \text{ cm/s}^2$.

The acceleration in this case is determined from a known relation:

$$a = 4\pi^2 f^2 A, \quad (1)$$

where f is vibration frequency;

A is vibration amplitude.

The piles were driven by a S-995 kick-atomizing pipe hammer (Fig. 2) with the following parameters: total hammer mass $Q = 2500 \text{ kg}$, hammer impact force $q = 1250 \text{ kg}$.




Fig. 2. Kick-atomizing pipe hammer S-995.

A. Measurement and recording equipment used in the experiment

B. Geological profile

As the residential and designed houses (Fig. 1) are located on even relief III of left-bank terrace of Kura river. The site surface is formed as embankment with the thickness of up to 1.5 m, then follow quaternary deposits represented by soft plastic clay. The thickness of clay varies from 4.5 m in the area of the residence house in Trialetskaya street to 10.5 m in the area of the residence house in Kaloubanskaya street and to 13.0 m in the intersection of the two streets. The noted soil is spread under by bedrock represented by argillites and sandstones weathered on the surface down to 2.5–3.5 meters.

To record the vibrations, conventional engineering and seismometric equipment was used including two light-beam oscilloscopes N-700, ten seismic detectors VEGIK and two seismic detectors K-001. The Seismic detectors with reflecting galvanometer GB-III-3 measure the displacement depth. The measurement profile consisted of 5 measuring sites, each of them including vertical and horizontal seismic detectors. Site 5 was located two meters away from the hammering location; site 4 was six meters away; site 3 was 16 meters away (sites 3–5 were mounted on the ground). Site 2 was located on a step of the building foundation (a smaller seismic detector K-001 was used and fixed by gypsum to the foundation), while site 1 was located on the building roof at the side edge of the building (Fig. 3).




Fig. 3. Arrangement scheme of source and recording equipment



Fig. 4. Digitized record, pile no. 2, depth of 4 m, vertical component




Fig. 5. Spectrum (a) and normalized spectrum (b) of digitized record, pile no. 2, depth of 4 m, vertical component

TABLE I. MAXIMUM AMPLITUDE OF VERTICAL VIBRATIONS (MM)

Measurement site No.	Depth of pile driving h [m]						
	First pile			Second pile			
	2	4	5	2	4	6	>6
1	0.0029	0.0021	0.0049	0.0029	0.0023	0.0025	0.0059
2	0.0018	0.0011	0.0018	0.0016	0.0009	0.0011	0.0027
3	0.003	0.0024	0.0027	0.003	0.0024	0.0048	0.0061
4	0.03	0.033	0.024	0.038	0.00362	0.110	0.023
5	0.145	0.156	0.11	0.18	0.18	0.413	0.263

TABLE II. MAXIMUM AMPLITUDE OF HORIZONTAL VIBRATIONS [MM]

Measurement site No.	Depth of pile driving h [m]						
	First pile			Second pile			
	2	4	5	2	4	6	>6
1	0.0056	0.0034	0.0034	0.0034	0.0046	0.0046	0.0047
2	0.0021	0.0018	0.0018	0.0036	0.0033	0.0030	0.0036
3	0.0079	0.0092	0.0066	0.0088	0.0088	0.0147	0.014
4	0.144	0.203	0.0867	0.084	0.1294	0.179	0.241

III. MEASUREMENT RESULTS

The seismic records were digitized (Fig. 4) and amplitude spectra were plotted (Fig. 5). Total measurement count amounted to 121 (e.g. Tables 1 and 2). The measurement channels were adjusted. The average frequency of vertical vibrations amounted to 18–20 Hz. The average frequency of horizontal vibrations amounted to 13–15 Hz. In the area adjacent to the pile driving locations, the maximum amplitude of vertical vibrations (site 5) amounted to 0.11–0.413 mm, 0.024–0.116 mm in measurement site 4, 0.0024–0.0061 mm in measurement site 3, 0.001–0.0027 mm in measurement site 2, i.e. on the foundation, 0.0021–0.0059 mm in measurement site 1 (floor slab of the 5th floor). The maximum amplitude of horizontal vibrations in site 5 was 0.084–0.241 mm, 0.006–0.0147 mm in site 3, 0.0018–0.0036 mm in site 2, 0.0034–0.0057 mm in site 1. We should note the presence of clear non-linearity in the clay soil under strong impact (site 5) which outstands by the shape of the spectral curve (Fig. 5a).

In the area adjacent to the pile (site 5), the acceleration of vertical vibrations amounts to 530 cm/s², (A = 0.413 mm, f = 18 Hz), which denotes the occurrence of residual deformations in the soil [24–25]. In the next observation point (No. 4), the acceleration amounts to 113 cm/s², (A = 0.127 mm, f = 15 Hz). In other words, at the distance of 6 meters away from the pile driving location, there are no residual deformations. Then (No. 3), we determined the acceleration directly in the soil under the building foundation, unlike the vibration of the free soil surface. Here it amounted to 31 cm/s² (A = 0.0048 mm, f = 14 Hz).

For the horizontal component in site 4, the acceleration amounted to 310 cm/s² (A = 0.241 mm, f = 18 Hz), i.e. on the basis of acceleration of the horizontal component at the distance of 6 meters, the residual deformations are also present and two times exceed the lower limit of the critical acceleration, which is also quite high. In the next observation point No.3, the acceleration amounts to 93 cm/s², (A = 0.014 mm, f = 13 Hz).

Let us determine the vibration decrement using the following formula:

$$\delta = \frac{1}{m} \ln \frac{a_n}{a_{n+m}} \quad (2)$$

where m is the number of cycles;

a_n, a_{n+m} is the amplitude of corresponding oscillation cycles.

The values of the decrement varied for the vertical component from $\delta = 0.47 - 1.87$ to $\delta_{av} = 1.2$, for horizontal from $\delta = 0.31 - 1.15$ to $\delta_{av} = 0.5$. The value of δ increases with the penetration depth.

Interestingly, the vibration decrement is maximum for high amplitudes and in soils with residual deformations. For small amplitudes, the decrement is considerably lower.

IV. PROPAGATION OF SEISMIC WAVES AND THEIR ABSORPTION

When analyzing the obtained results, one should note the specificities of the observed process. First, these are vibration amplitude, their frequency and absorption by the environment of the initial signal. The absorption depends on both distance and time. The second absorption type is when the law of wave shape alteration is harmonic $A = A_0 e^{-ht} \cos \omega t$ (h is attenuation factor, A_0 is vibration amplitude in the vibration origin). We have already assessed this type of absorption (vibration decrement) and $\delta = \frac{K}{f}$ (f is wave frequency). Consequently, the average signal attenuation coefficient (signal in this soil) will amount for vertical and horizontal components $K_v = 21.6$ and $K_h = 7$, correspondingly.

Taking into account that we use pulsed source, it could be represented by a spherical axially symmetric source (together with connected soil mass). However, the presence of preliminarily bored well creates so-called “long linear source” for considered distances (Fig. 6a).

It is a source of cylindrical fronts (Fig. 6b), which will give us cylindrical divergence, which changes the intensity of corresponding waves in the following way:

$$\frac{J_2}{J_1} = \frac{r_1}{r_2} \quad (3)$$

Hence, taking into account that the intensity is the amplitude squared $I = A^2$, we derive the amplitude change in a remote point (A^2) relatively to the initial one (A_1):

$$\frac{A_2}{A_1} = const = \sqrt{\frac{r_1}{r_2}} \quad (4)$$




Fig. 6. Scheme of sources with connected mass of soil

By substituting values $r_1 = 2$ m and $r_2 = 6$ m gives $\frac{A_2}{A_1} = 0.57$. At distances $r_1 = 2$ m and $r_2 = 6$ m: $\frac{A_2}{A_1} = 0.35$.

For site 4, the decrease of the signal connected with cylindrical divergence will amount to 0.57, and 0.35 for site 3. With distance from the source it remains the same. This also increases the contribution to the change of the initial signal due to purely absorbing properties of the soil.

Taking into account that the geological profile of the plot is represented by two layers, let us estimate the coefficients of transmission T and reflection R of seismic waves by known equations [3]:

$$T = \frac{2V_1\rho_1}{V_1\rho_1 + V_2\rho_2}, \quad R = \frac{V_2\rho_2 - V_1\rho_1}{V_2\rho_2 + V_1\rho_1} \quad (5)$$

In the upper layer, the wave velocity $V_1 = 200$ m/s, density $\rho_1 = 1.8 \cdot 10^3$ kg/m³; in lower layer, $V_2 = 1800$ m/s and $\rho_2 = 2.3 \cdot 10^3$ kg/m³. Then $T = 0.16$ and $R = 0.84$.

Taking into account the above, the amplitude of waves induced in the soil will change as follows:

$$A = \sqrt{\frac{r_1}{r_2}} \cdot T \cdot A_0 e^{-\eta x} \quad (6)$$

where A_0 is the amplitude in the initial point.

η is the absorption coefficient in the medium\

x is the distance between reception points.

The vibrations of the slab of the 5-storey building in general repeat the oscillation of foundation soil, but exceed the soil vibration amplitude 2.2. times. This also complies with reference [26].

The base near the foundation of the residence house for this source represents a far zone. The absorption coefficient can be determined as follows [2]:

$$\alpha = 2.4 \cdot f \cdot 10^{-3} \quad (8)$$

where f is vibration frequency.

V. PROPAGATION OF SEISMIC WAVES WITH SHIELDING

At the distance of 11 meters from the source, at the depth of 3 meters in a reinforced-concrete rectangular duct, there is a metal heat pipe with diameter $\delta = 400$ mm (Fig. 1) which virtually is a shield from propagating waves [27]. Thus, we have performed calculations with and without accounting the shield.

For site 4 in relation to site 5: $A = 0.11$, $\sqrt{\frac{r_1}{r_2}} = 0.57$, $A_0 = 0.413$ m; $R = 0.84$; $T = 0.16$ (one reflection).

For site 3 in relation to site 4: $A = 0.0048$, $\sqrt{\frac{r_1}{r_2}} = 0.35$, $R = 0.52$; $T = 3 \cdot 0.16$ (three reflections).

a) without shield (the trapezium is the pipeline duct)

$$0.11 = 0.57 \cdot 0.84 \cdot 0.413 e^{-4\eta}$$

$$\eta_1 = 0.15$$

and

$$0.0048 = 0.35 \cdot 0.52 \cdot 0.413 e^{-14\eta}$$

$$\eta_2 = 0.2$$

here $\eta_2 > \eta_1$

b) with shield (concrete $E = 200\,000$ kg/cm, $\rho = 2.5$ T/m³, $\mu = 0.18$, $T = 0.125$ and $V_s = 2170$ m/s)

$$\eta_1 = 0.15$$

and

$$0.0048 = 0.35 \cdot 0.27 \cdot 0.413 e^{-14\eta}$$

$$\eta_2 = 0.15$$

$$[T = 4 \cdot 0.16 + 2 \cdot 0.125 = 0.73; R = 0.27]$$

$\eta_1 = \eta_2$ i.e. absorption is similar in virtually similar soil.

In other words, with accounting of reflections from the duct walls $\eta_1 = \eta_2$, which testifies the adequateness of the data.

c) Then, let us calculate the amplitude that would be without the duct in measurement site No. 3.

$$A = 0.35 \cdot 0.52 \cdot 0.413 e^{-14 \cdot 0.15}$$

$$A = 0.0092 \text{ mm}$$

and acceleration $a = 39.4384 \cdot 11^2 \cdot 0.0092 = 4.4$ cm/s². Let us determine the acceleration magnitude at the distance of 11 m:

$$4.4 = 0.35 \cdot 0.52 \cdot A_0' e^{-5 \cdot 0.15}$$

$$A_0' = 51 \text{ cm/s}^2$$

This, the acceleration of vertical oscillations is almost 3 times lower than the critical one.

Vertical component $H = 2$ m.

$$\text{a) without shield } 0.03 = 0.57 \cdot 0.84 \cdot 0.145 e^{-4\eta}$$

$$\eta = 0.21$$

$$0,003 = 0.35 \cdot 0.52 \cdot 0.145 e^{-14\eta}$$

$$\eta = 0.155 \approx 0.16$$

b) with shield

$$0.003 = 0.35 \cdot 0.27 \cdot 0.145 e^{-14\eta}$$

$$\eta = 0.11$$

Hence, with $H = 2$, the obstacle will not impede the wave propagation and the duct has no effect.

Horizontal component $H = 2$ m.

$$\text{a) without shield } 0.0147 = 0.35 \cdot 1 \cdot 0.19 e^{-14\eta}$$

$$\alpha = 0.104 \text{ m}^{-1}$$

$$\text{b) with shield } 0.0147 = 0.35 \cdot 0.715 \cdot 0.179 e^{-14\eta}$$

with the obstacle

$$\alpha = 0.08 \text{ m}^{-1}$$

Let us estimate A at the distance of 11 m from the source:

$$0.0147 = 0.35 \cdot 0.715 \cdot A_0' e^{-5 \cdot 0.008}$$

$$A_0' = 0.088 \text{ mm}$$

$$A_0' = 78 \text{ cm/s}^2 \approx 80 \text{ cm/s}^2$$

Horizontal component $H > 6$

$$\text{a) without shield } 0.0102 = 0.35 \cdot 1 \cdot 0.226 e^{-14\eta}$$

$$\eta = 0.146 \approx 0.15$$

$$\text{b) with shield } 0.0102 = 0.35 \cdot 0.715 \cdot 0.226 e^{-14\eta}$$

$$\eta = 0.122 \approx 0.12$$

c) worst-case scenario. $\eta = 0.12$

$$A = 0.35 \cdot 0.715 \cdot 0.226 e^{-5 \cdot 0.12}$$

$$A = 0.031$$

$$a = 28 \text{ cm/s}^2 = 30 \text{ cm/s}^2$$

Thus, the study results have demonstrated that during pile driving, the induced vibrations in the foundation soil and in the building itself do not reach values posing danger for the integrity of buildings most closely located to the pile driving

location and are quite safe. Indeed, the construction of the high-rise building was consequently realized under total absence of any deformations in existing buildings.

VI. CONCLUSIONS

The average frequency of vertical vibrations amounted to 18–20 Hz, while that of horizontal ones amounted to 13–15 Hz.

The amplitudes of horizontal vibrations, as a rule, exceed those of vertical vibrations 1.5–2 times. The only exclusion is the site located at distance $R = 6$ m from the source. There the exceeding reaches 5 times. This, evidently, is explained by high-power non-linear deformations in horizontal direction at introduction of the pile into the bored well and extension of its edges as a side thrust.

The acceleration of vertical vibrations amounted at the distance of 2 m from the source $A = 530 \text{ cm/s}^2$ and 113 cm/s^2 at the distance of 6 m from the source. Thus, at the distance of 6 meters, the amplitude of soil vibration acceleration is less than critical (150 cm/s^2) and leaves no residual deformation.

The analysis of data has shown that during the pile driving for high-rise building foundation, the induced vibrations in the foundation soil and in the closest 5-storey building are rather safe. Indeed, the building of the high-rise building was realized with total absence of any deformations in the existing buildings surrounding the tested construction site.

References

- [1] A.V. Gorbatikov, E.A. Rogozhin, M.Yu. Stepanova, Yu.V. Harazova, N.V. Andreeva, F.V. Perederin, V.B. Zaalishvili, D.A. Melkov, B.V. Dzeranov, B.A. Dzeboev, A.F. Gabaraev, "Peculiarities of deep structure and modern tectonics of Greater Caucasus in Ossetia sector on a complex of geophysical data", *Earth Physics*, no. 1, p. 28, 2015.
- [2] V.B. Zaalishvili, *Physical principles of seismic microzonation*. Moscow: IEF RAS, 2000, 367 p.
- [3] V.B. Zaalishvili, "Dependence of spectral characteristics of seismic waves on the structure of the upper section part", *Geology and geophysics of southern Russia*, no. 4, pp. 15–44, 2014.
- [4] V.B. Zaalishvili, "Correlation dependencies between linear and non-linear characteristics of soils using instrumental data", *Geology and geophysics of southern Russia*, no. 4, pp. 45–57, 2014.
- [5] V.B. Zaalishvili, A.V. Odisharia, I.E. Timchenko, M.G. Otinashvili, S.A. Gogmachadze, Z.V. Zaalishvili, "Engineering macroseismic survey of epicentral zone of earthquake on December 14th, 2000", *Geology and geophysics of southern Russia*, no. 1, pp. 30–38, 2014.
- [6] V.B. Zaalishvili, "Some problems of practical realization of seismic microzoning: factors forming the intensity of earthquake", *Geology and geophysics of southern Russia*, no. 3, pp. 3–39, 2014.
- [7] V.B. Zaalishvili, T.T. Magkoev, D.A. Melkov, F.S. Morozov, "Mechanisms of formation of non-linear and inelastic phenomena conditioned by nanosized particles under intense actions", *Geology and geophysics of southern Russia*, no. 1, pp. 48–60, 2016.
- [8] V.B. Zaalishvili, D.A. Melkov, V.D. Makiev, "Macro seismic manifestation of seismic events conditioned by the effect of soil conditions and formation of maps of seismic microzoning", *Geology and geophysics of southern Russia*, no. 1, pp. 48–55, 2018.
- [9] V. Zaalishvili, D. Melkov, A. Kanukov, B. Dzeranov, "Spectral-temporal features of seismic loadings on the basis of strong motion wavelet database", *International Journal of Geomatics*, vol. 10, no. 19, pp. 1656–1661, February, 2016.
- [10] G.P. Ganapathy, V.B. Zaalishvili, D.A. Mel'kov, B.V. Dzeranov, S.S. Chandrasekaran, "Mapping of soil liquefaction potential

- susceptibility for urban areas”, *Geology and geophysics of the South of Russia*, no. 3, pp. 106–115, 2018.
- [11] V.Zaalishvili, D. Melkov, I. Gabeeva, “Expected seismic intensity assessment taking into account local topography site effect” *International Journal of Geomate*, vol. 10, no. 19, pp. 1680–1686, February, 2016.
- [12] V.B.Zaalishvili, D.A. Melkov, A.S. Kanukov, “Database of the network of seismic observations “Vladikavkaz””, *Geology and geophysics of southern Russia*, no. 4-2, pp. 14–18, 2014.
- [13] V.B.Zaalishvili, A.K. Dzhgamadze, D.A. Melkov, B.V. Dzeranov, A.F. Gabaraev, I.L. Gabeeva, B.A. Dzeboev, A.S. Kanukov, V.D., Shepelev, “Refinement of engineering and geological conditions of territory using microseisms (exemplified by settlements of Republic of North Ossetia-Alania)”, *Geology and geophysics of southern Russia*, no. 1, pp. 5–20, 2015.
- [14] V.B. Zaalishvili, D.A. Melkov, A.S., Kanukov, B.V. Dzeranov, V.D. Shepelev, “Application of microseismic and calculational techniques in engineering-geological zonation”, *International Journal of GEOMATE*, vol. 10, no. 1, pp. 1670–1674, 2016.
- [15] S.J. Brandenberg, J. Coe, R.L. Nigbor, K. Tanksley, “Different Approaches for Estimating Ground Strains from Pile Driving Vibrations at a Buried Archeological Site”, *Journal of Geotechnical and Geoenvironmental Engineering*, vol. 135, no. 8, pp. 1101–1112, 2009.
- [16] Y. Choi, M.W. O'Neill, “Response of soil plug to horizontal and vertical excitation”, *Proceedings of the Seventh. International Society Offshore & Polar Engineers*, pp. 772–777, 1997.
- [17] B. Farmani, N.O. Kitterod, E. Gundersen, “Detection of geological structures using impact-driven piling as a seismic source”, *Near Surface Geophysics*, vol. 14, no. 4, pp. 315–325, 2016.
- [18] D. Nottingham, “Dfi. Improvements in deep compaction using vibratory pile hammers”, *Dfi 2004: Deep Foundations Institute, Conference Proceedings*, pp. 93–98, 2004.
- [19] V.B.Zaalishvili, Ya.L. Krantsfeld, “Geophysical principles of engineering seismic protection of critical construction objects”, *Geology and geophysics of southern Russia*, 2014, no. 1, pp. 39–50.
- [20] V.B.Zaalishvili, O.G. Burdzieva, T.V. Zaks, A.S. Kanukov, “Information monitoring of distributed physical fields within urbanized territory”, *Geology and geophysics of southern Russia*, no. 4, pp. 8–16, 2013.
- [21] T.V.Zaks, O.G. Burdzieva, V.B. Zaalishvili, “Impact of noise, gamma radiation and other geophysical factors on population health”, *AKUSTIKA*, vol. 32, pp. 206–210, March 2019.
- [22] Ia.Sh.Ziyazov, V.F. Kovalev et al., *Methodological recommendations on pile driving near buildings, structures and underground communications*, Ufa: NIIPromstroy, 1979.
- [23] *Manual on pile driving near buildings and structures*. VSN 358-76 MMSS SSSR, Moscow, 1977.
- [24] R. Sheriff, L. Geldart, *Seismology*. Moscow: Mir, 1987.
- [25] V.B. Zaalishvili, *Seismic microzoning using data of artificial induction of oscillation of ground*. Dissert. Cand. Sci. Tbilisi, 1986.
- [26] N.N. Goryainov, F.M. Lyakhovitskiy, *Seismic methods in engineering geology*. Moscow: Nedra, 1979, 143 p.
- [27] V.B.Zaalishvili, D.A. Melkov, A.F. Gabaraev, “Finite element analysis of open trench seismic vibrations barriers”, *AKUSTIKA*, vol. 32, pp. 282–285, March 2019.